

C-Plank Typical NBS Format

K40 SUSPENDED, CEILINGS

To be read with Preliminaries/General conditions.

TYPE(S) OF LINING/PANELLING

160 UPVC FOODSAFE PANELLING TO WALLS

Structural Soffit

Panels:

Manufacturer and reference: to be supplied by:

Hygienik Systems Limited

Unit 10

Royds Enterprise Park

Future Fields

Beacon Road

Bradford

BD6 3EW

01274 355777 Contact Tony Doherty

Hygienik C-Plank 250mm Tongue and groove PVC Twin wall Plank

(Secret Fixed)

Colour: White, Decorative marble, gold/silver infill

Size: C-Plank are 250mm wide supplied in lengths of 4000mm 3000mm

Thickness 10mm

Method of fixing: Secret fixed through backs of tongue with wafer head self-drilling point zinc plated 4.2x13 to structural Soffit.

Components/Accessories PVC Profiles for corners drawing

C105, C205, C305, C405. Access Panels available on request,

Service fittings Luminaries and air diffusers supplied by others,

Apertures for luminaries and air diffusers trimmed out with MF6A perimeter

Channel, additional hangers to be installed at corners of Apertures.

Provision of Fixings points for surface mounted lighting in the form of MF5 Ceiling section to be incorporated within ceiling grid at time of installation

PRELIMINARY/GENERAL REQUIREMENTS

PROTECTION:

Do not deliver components to site and do not remove protective packaging/ coverings until immediately before required for fixings.

Stack boards and panels flat on bearers and separated by spacers where necessary to prevent damage to or from projections.

Keep components and completed linings/panelling clean and dry, and protect from physical damage until Practical Completion.

ENVIRONMENT:

Do not start work specified in this section before building is weather tight, wet trades have finished their work and the building is well dried out.

Structural Soffit: Timber joists @ 600mm Centres, Steel Floor, Z Purlin, Gyproc MF systems suspended in accordance with manufactures. (Min 14 c InstallationTemp)