

K-Panel Typical NBS Format

K13 RIGID SHEET FINE LININGS/PANELLING

To be read with Preliminaries/General conditions.

TYPE(S) OF LINING/PANELLING

160 UPVC FOODSAFE PANELLING TO WALLS

Background: Flat and plumb Brickwork/Block work Plasterd/Renderd walls, Boarded out stud partitions. Wall must be flat and plumb

Panels:

Manufacturer and reference: to be supplied by:

Hygienik Systems Limited

Unit 10

Royds Enterprise Park

Future Fields

Beacon Road

Bradford

BD6 3EW

01274 355777 Contact Tony Doherty

Hygienik Panel K-Panel Class 1 fire rated UPVC Panels Mechanically fixed colour, White, Blue, Green, Ivory, Grey, and (Marble & Pattern available on request)

Thickness: 2mm, 2.5mm, 3mm

Size: Width 1220mm Height 2400mm, 3000mm

Method of fixing panels: Mechanically fixed using PVC carriers

Components/Accessories: preformed angle sections int/ext corners, UPVC cill detail, Joints & edge trims Drawing K105, K205, K305, and K405.

Included features: seal all round perimeter joints on completion with sealant as specified BS "food safe" comply with EEC regulations for hygiene in food production areas. Directive No 64/483 and the requirements as outlined in statutory instruments 454 and 805 (food Hygiene)

PRELIMINARY/GENERAL REQUIREMENTS

PROTECTION:

Do not deliver components to site and do not remove protective packaging/ coverings until immediately before required for fixings.

Stack boards and panels flat on bearers and separated by spacers where necessary to prevent damage to or from projections.

Keep components and completed linings/panelling clean and dry, and protect from physical damage until Practical Completion.

ENVIRONMENT:

Do not start work specified in this section before building is weather tight, wet trades have finished their work and the building is well dried out. Install Panels at temperature comparable to finish working environment. (Min 14°C)