

NBS SPECIFICATION CLAUSE FOR HYGIENIK C-PLANK – WALL LINING APPLICATIONS – 01.02.12

K13 Rigid sheet fine linings and panelling

To be read with Preliminaries/ General conditions.

TYPES OF LINING AND PANELLING

145 PROPRIETARY PLASTICS WALL CLADDING: C-PLANK.

- Substrate: Blockwork / Concrete / Timber / Stud / Plasterboard / Plywood
- Battens: Timber / Galvanised Steel Top Hats
- Panels:
- Manufacturer: **Hygienik Systems Limited**
Unit 3a, A1 Business Park, 370 Bradford Road, Brighouse, West Yorkshire, HD6 4DJ
Telephone: 01274 355777 Email: matt@hygienee.com www.hygienee.com

Product reference: **C-Plank For Walls**

- Thickness: 10mm.
- Colour/ Pattern/ Finish: White / Plain / Semi Gloss
- Edge treatment: Tongue and Groove.
- Installation:
 - Method of fixing panels: Concealed, Secret Fix.
 - Joint treatment: C-Plank Edge, Jointing, Corner and Base Track profiles.
- Accessories: To be used with 'Food Safe' Sealants.

GENERAL REQUIREMENTS

230 CONTROL SAMPLES

- Sample area: Complete as part of the finished work.
 - Clause reference: K13/145.
 - Location: To Be Determined by Contractor
 - Size (minimum): 2 Square Metres
 - Included features: Typical Joint
- Approval of appearance: Obtain before proceeding.

260 ENVIRONMENTAL CONDITIONS

- General requirements prior to starting work specified in this section: Building weathertight; wet trades completed and affected areas dried out.
- Temperature and humidity before, during and after fixing lining/ panelling: Maintained at levels approximating to those which will prevail after building is occupied.

370 SEALANT POINTING

- Sealant: Food Safe Sealant.
 - Manufacturer: Contractors Choice.
 - Product reference: BS5889 Compliant Food Safe Sealant.
 - Colour: White / other colours available
- Application: As section Z22.